

This authorizes the application of the Certification Mark(s) shown below to the models described in the Product(s) Covered section when made in accordance with the conditions set forth in the Certification Agreement and Listing Report. This authorization also applies to multiple listee model(s) identified on the correlation page of the Listing Report.

This document is the property of Intertek Testing Services and is not transferable. The certification mark(s) may be applied only at the location of the Party Authorized To Apply Mark.

Applicant: Clark Reliance LLC

Manufacturer: Clark-Reliance LLC

Address: 16633 Foltz Parkway
Strongsville, Ohio 44149

Address: 16633 Foltz Parkway
Strongsville, Ohio 44149

Country: USA

Country: USA

Party Authorized To Apply Mark: Same as Manufacturer

Report Issuing Office: Intertek Testing Services NA, Inc., Cortland, NY

Control Number: 5014669

Authorized by: 

for L. Matthew Snyder, Certification Manager



This document supersedes all previous Authorizations to Mark for the noted Report Number.

This Authorization to Mark is for the exclusive use of Intertek's Client and is provided pursuant to the Certification agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Authorization to Mark. Only the Client is authorized to permit copying or distribution of this Authorization to Mark and then only in its entirety. Use of Intertek's Certification mark is restricted to the conditions laid out in the agreement and in this Authorization to Mark. Any further use of the Intertek name for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. Initial Factory Assessments and Follow up Services are for the purpose of assuring appropriate usage of the Certification mark in accordance with the agreement, they are not for the purposes of production quality control and do not relieve the Client of their obligations in this respect.

Intertek Testing Services NA Inc.
545 East Algonquin Road, Arlington Heights, IL 60005
Telephone 800-345-3851 or 847-439-5667 Fax 312-283-1672

| | |
|---------------------------|--|
| | <p>Intrinsically Safe Apparatus and Associated Apparatus for Use in Class I, II, and III, Division 1, Hazardous (Classified) Locations [UL 913:2013 Ed.8+R:06Dec2019]</p> <p>Explosion-Proof and Dust-Ignition-Proof Electrical Equipment for Use in Hazardous (Classified) Locations [UL 1203:2013 Ed.5+R:19Aug2020]</p> <p>Explosive Atmospheres – Part 0: Equipment – General Requirements [UL 60079-0:2019 Ed.7+R:15Apr2020]</p> <p>Standard for Safety Explosive Atmospheres - Part 1: Equipment Protection by Flameproof Enclosures “d” [UL 60079-1:2015 Ed.7+R:23Jan2020]</p> <p>Standard(s): Explosive Atmospheres - Part 11: Equipment Protection by Intrinsic Safety "i" [UL 60079-11:2013 Ed.6+R:14Sep2018]</p> <p>Explosive Atmospheres — Part 0: Equipment — General Requirements [CSA C22.2#60079-0:2019 Ed.4]</p> <p>Explosive Atmospheres - Part 1: Equipment Protection by Flameproof Enclosures "d" (R2021) [CSA C22.2#60079-1:2016 Ed.3]</p> <p>Explosive Atmospheres - Part 11: Equipment Protection by Intrinsic Safety "i" (R2018) [CSA C22.2#60079-11:2014 Ed.2]</p> <p>Explosion-proof Equipment [CSA C22.2#30:2020 Ed.4]</p> |
| <p>Product:</p> | <p>MAGNETOSTRICTIVE TRANSMITTER</p> <p>For Use In: Class I, Div. 1, Groups C, D, T4; Class I, Zone 1, AEx db ia IIB T4 Gb; Ex db ia IIB T4 Gb;</p> <p>Rated ambient temperature range: -40°C to +60°C</p> |
| <p>Brand Name:</p> | <p>Jerguson</p> |
| <p>Models:</p> | <p>JMT- followed by G or T; followed by A2, S2; followed by A, B, C, D, E, F, G, H, I, J, K, L, M, N, O, P, Q, R, S, T, U, V, W, X, Y, Z; followed by 12 to 360; followed by 12 to 360; followed by A, B, C, D, E, F, G, H, I, J, K, L, M, N, O, P, Q, R, S, T, U, V, W, X, Y, Z; followed by S, D; followed by 0, 1, 3; may be followed by R; may be followed by S.</p> |