

JMT™ Series

Magnetostrictive Transmitter




**Elevate Accuracy with
Magnetostrictive
Level Measurement:
*Precision You Can Count On***

JERGUSON®

A PRODUCT OF CLARK-RELIANCE

JERGUSON®


A PRODUCT OF CLARK-RELIANCE




JMT Series Magnetostrictive Transmitter

The JMT Series magnetostrictive transmitter represents a significant advancement in level measurement technology. The integration of Jerguson's signal capture technology sets it apart with its superior signal-to-noise ratio, ensuring highly accurate level readings even in challenging environments. The dual-entry enclosure design enhances its functionality by offering both safe and convenient access to the HMI on the front and easy access to power connections in the back. The HMI enhances user interaction by offering instant access to vital information, such as current level readings and device settings, all at the touch of a button. The real-time waveform graph is an especially useful tool for monitoring and diagnostics, offering a visual representation of the process in action.

Compatibility with HART 7 makes the JMT highly versatile and easy to integrate into existing systems, facilitating seamless communication and control. The transmitter is also designed with user-friendliness in mind, from installation to setup, ensuring that it can be quickly and efficiently deployed in various applications. In line with Jerguson's reputation for reliability, the JMT complements our established range of flag indicators, floats, and switches, adding a robust solution for continuous level control.



- View Full waveform, including trigger level and # of peaks
- LIVE View of signal, noise condition



- Quickly Display Current Device Parameters
- Verify Range, URV, LRV
- Verify SN, Tag#

Unlock Smarter Device Management with Pactware Compatibility

We're excited to announce that JMT now supports **iDTM (Device Type Manager)** integration, enabling seamless operation within **Pactware** and other FDT-compliant systems.

This enhancement brings smarter, faster, and more intuitive device configuration to your fingertips.



Download Here

www.clarkreliance.com/dtm-download

- 4-20 mA loop powered; 12.5 to 36VDC
- HART Protocol Communication NEW! HART 7
- Sensing lengths from 12 inches (305mm) to 360 inches (9 meters)
- Process Temperature -300°F to 700°F (-185°C to 372°C) (Insulation Safeguards Required over 350°F [176°C]) - Gage Mount
- Process Temperature -40°F (-40°C) to 285°F (140°C) - Tank Mount
- Dual Float Functionality (Interface and Total Level)
- ETL approved for USA, Canada, ATEX and IECEx (Explosion/Flame Proof, Intrinsic Safety)
- Dual Compartment NEMA 4X; IP66 Enclosure
 - Epoxy Coated Aluminum Standard
 - 316SS optional
- One-Touch Waveform Graphical Display

Hazardous Area Certifications

Explosion Proof



ETL (USA, Canada)

- Class I, Div. 1 and 2, Groups B, C, D; T6
- Class I, Zone 1, AEx db IIB+H2 T6
Ex db IIB+H2 T6 Gb
- -40°C ≤ Ta ≤ +60°C
(-40°F ≤ Ta ≤ +140°F)



ATEX

- II 2 G Ex db IIB+H2 T6 Gb
- -40°C ≤ Ta ≤ +60°C
(-40°F ≤ Ta ≤ +140°F)



IECEx

- Ex db IIB+H2 T6 Gb
- -40°C to +60°C
(-40°F to +140°F)

Intrinsic Safety

ETL (USA, Canada)

- Class I, Div. 1 and 2, Groups C, D, T4
- Class I, Zone 1, AEx db ia IIB T4 GB
Ex db ia IIB T4 Gb
- -40°C ≤ Ta ≤ +60°C
(-40°F ≤ Ta ≤ +140°F)

ATEX

- II 2 G Ex db ia IIB T4 Gb
- -40°C ≤ Ta ≤ +60°C
(-40°F ≤ Ta ≤ +140°F)

IECEx

- Ex db ia IIB T4 Gb
- -40°C ≤ Ta ≤ +60°C
(-40°F ≤ Ta ≤ +140°F)

How to Specify JMT Magnetostrictive Transmitter

JMT G - A2 A - ### / 03650 - S S 1

Mounting Style

Code Description

G	Gage Mount 316L/316SS Sensor Housing
T	Tank Mount 316/316SS Sensor Housing

Housing

Code Description

A2	Aluminum Dual Compartment
S2	Stainless Steel Dual Compartment

Transmitter Orientation

Code Description

A	Top Left Hand (Standard)
B	Top Right Hand
C	Bottom Right Hand
D	Bottom Left Hand

*Tank Mount only available with selection A or B

Max Sensing Range

12" to 360" (304.8mm to 9144mm)
In 1-Inch Increments (Example: 48" = 048)
(Determined by manufacturer)

Measuring Range

Order Length: 12" to 360" (305mm to 9144mm)
On 1-Inch Increments, in Hundredths of an Inch (Example: 36.5" = 03650)

Area Classification

Code Description

0	Ordinary Location (IP66/Type 4X)
1	North American Explosion Proof/Flame Proof (IP66/Type 4X)
2	North American Intrinsic Safety (IP66/Type 4X)
3	ATEX / IECEx Flame Proof (IP66/Type 4X)
4	ATEX / IECEx Intrinsic Safety (IP66/Type 4X)

Level

Code Description

S	Single Level
D	Dual Level

Process Temperature (A-Z)

Code Description

S	Standard
H	High Temperature (Insulation Blanket Required for Processes over 350°F [176°C])
C	Cold Temperature (Thermowell Included - Insulation Safeguards Required)
V	Vibration (Special Mounting)

*Tank Mount only available with selection S

See following page for Tank Mount Connection Kit

Specifications

Electronics

Supply Voltage: 12.5 - 36 Vdc (12.5 V @ 20mA)

Repeatability: .005% of full scale or .010", whichever is greater

Non-Linearity: .01% of full scale or .030", whichever is greater

Damping: 1 to 32 Seconds

Operating Temp: -50°C to 85°C (-58°F to 185°F)

RFI Guide: SAMA PMC 31.1-5.1
20 to 1000 Mhz to 30 V/m

Humidity Guide: SAMA PMC 31.1-5.2

Housing

- Dual compartment explosion proof housing
- 3/4" NPT conduit entry
- Epoxy coated aluminum (Standard); 316SS (Optional)
- Nema 4X; IP66

Sensor Probe Specification

Gage/Tank Mount Material: 316L/316SS Standard

Vibration Guide: SAMA PMC 31.1-5.3

See Sales Drawing A-35152-SALES for BOM and Dimensional Information

JMT™ Series

JMT In-Tank Process Connection & Accessory Kit

Example Model Code: JMT T-A2A-048/03650-SS1+ TA - 20 - F 1 - 0

Float(s) / Application

XX 2-Character Float Code for Single (Overall) Level (Table 1)

XXX 3-Character Code for Single (Interface) Level (Table 2)

XXXX 4-Character Code for Dual (OAL+IF) Level (Table 3)

Table 1 - Float Code: Single (Overall) Level					
	Mat'l	316SS			
	OD	1.85	2.06	2.05	3.60
	PSIG	400	750	350	300
Min SG	0.73	TA	---	---	---
	0.84	---	TB	---	---
	0.68	---	---	TC	---
	0.49	---	---	---	TD

Table 2 - Float Code: Single (Interface) Level							
Material (Parts In Contact):				316SS			
Float Outside Diameter:				2.05" / 52.1mm			
Max Operating Pressure:				350 PSIG / 24.1 Bar			
SG Sinks Thru	0.60	0.70	0.80	0.90	1.00	1.10	1.20
SG Floats On	0.70	0.80	0.90	1.00	1.10	1.20	1.30
Float Code	TC1	TC2	TC3	TC4	TC5	TC6	TC7

Table 3 - Float Code: Dual (OAL+IF) Level								
		Float Code, Interface						
		TC1	TC2	TC3	TC4	TC5	TC6	TC7
Float Code, OAL	TA	TAC1	TAC2	TAC3	TAC4	TAC5	TAC6	TAC7
	TB	TBC1	TBC2	TBC3	TBC4	TBC5	TBC6	TBC7
	TC	TCC1	TCC2	TCC3	TCC4	TCC5	TCC6	TCC7
	TD	TDC1	TDC2	TDC3	TDC4	TDC5	TDC6	TDC7

Options

- 0 Omitted (None)
- Stop Collar Only
- C225 Centering Disc 2.25" OD (Suitable for Float Codes Starting with TA, TB, & TC)
- C375 Centering Disc 3.75" OD (Suitable for Float Codes Starting with TD)
- S¹⁻⁴ Stilling Well + Centering Disc (Hole Spacing is 60" (Overall Level) or 8" (IF or Dual))

Process Connection Class

- 0 Omitted (Threaded)
- 1 150#
- 3 300#
- 6 600#

Process Connection Style

- T Threaded, MNPT
- F Flanged
Threaded compression fitting through flange/adaptor
- W Flanged, Seal-Welded
Socket-weld compression fitting through flange/adaptor

Process Connection Size


- 05 0.5 (Threaded Only)
- 20 2.0 (Threaded or Flanged)
- 25 2.5 (Flanged Only)
- 30 3.0 (Flanged Only)
- 35 3.5 (Flanged Only)
- 40 4.0 (Flanged Only)
- 50 5.0 (Flanged Only)
- 60 6.0 (Flanged Only)

Notes:

- 1 - Available with Process Connection Style 'F' or 'W', for Process Connection Size '25', or larger.
- 2 - Stilling Well OD is either 2.5" or 4.0" (nominal). Smallest OD, larger than float OD, shall be used.
- 3 - Centering disc OD matched to stilling well.
- 4 - Not Available for float(s) with larger OD's.

Fill out specification form M200.08 to accommodate for storage vessel geometry (required).

JMT™ Series




JMT Method of Operation

The on-board electronic module sends a low-power pulse down the sensing wire of the transmitter. The float, which is designed to reside precisely at the fluid level, contains internal magnets outwardly projecting a strong magnetic field. Where the float's magnetic field intersects the sensing wire, a torsional return "pulse" results, and travels back towards the electronics, where it is measured. The "time of flight" is used to determine the position of the float.

Mounting Styles

The JMT Magnetostrictive Transmitter can be mounted via direct Insertion into a storage vessel, or externally to a Magnetic Level Gage with a variety of connection types. When installed to the Jerguson Magnicator, the unique magnetic arrangement allows for almost any chamber combination, including Schedule 160, without sacrificing reliability. A highly reliable and accurate means to add continuous level measurement to almost any application.



MORE Jerguson® SOLUTIONS



Jerguson®
360™ Valve



Jerguson® MGWR-S
Single Chamber Design



Jerguson® MiniMag
Light Duty Magnetic Level Gauge



Jerguson® LumaStar™
Level Gage Illuminators

JERGUSON®
A PRODUCT OF CLARK-RELIANCE

16633 Foltz Parkway, Strongsville, OH 44149 USA Phone: +1 440.572.1500 Fax: +1 440.238.8828
www.jerguson.com



ISO 9001:2015