

## SPECIFICATIONS

### DIMENSIONS:

Height: 20" (510mm)

Width: 16" (410mm)

Depth: 25" (635mm)

Weight: 75lbs (34kg)

Enervac International ULC  
280 Holiday Inn Drive  
Cambridge, Ontario  
Canada  
N3C 1Z4  
(P)1-519-651-1034  
(F)1-519-651-1038

www.enervac.com  
sales@enervac.com



For more  
information  
scan the  
code!

## SF<sub>6</sub> GAS TRANSFER UNIT - GTU



Designed as a low cost solution to recovering, consolidating and transferring Sulfur Hexafluoride, the GTU is an essential tool for servicing small volume SF<sub>6</sub> equipment.

### APPLICATIONS:

- Recover SF<sub>6</sub> gas to an optionally available auxiliary storage tank
- Pressure regulated recharging of SF<sub>6</sub> gas to switch gear
- Consolidation of storage cylinders
- Purification of SF<sub>6</sub> (removes particles, moisture, and SF<sub>6</sub> decomposition products)

### FEATURES:

- Rugged steel enclosure.
- Regulated inlet for direct connection to high-pressure bottles without throttling.
- High discharge pressure for liquefaction in high ambient temperatures.
- Color change moisture indicator to monitor moisture in the gas.
- Can be used with SF<sub>6</sub> tanks, bottles or carts.
- Automatic shut off when maximum allowable pressure is reached.
- High pressure, direct-drive oil-less compressor with 1000:1 compression ratio (capable of
- 1000psi – 69 bar)
- Purifies, dries and filters to 0.1 microns during recovery and re-pressurization
- Filters are easily changed without disconnecting any tubing or using any special tools
- Comes complete with 9.8ft / 3m hoses and power cable