

SPECIFICATIONS

STANDARD VOLTAGE:

All voltage and frequency combinations supported.

SYSTEM PERFORMANCE:

- < 0.5 mbar recovery capability.
- < 0.0001 mbar vacuum capability

Enervac International ULC 280 Holiday Inn Drive Cambridge, Ontario Canada N3C 1Z4 (P)1-519-651-1034 (F)1-519-651-1038

www.enervac.com sales@enervac.com



For more information scan the code!

SF₆ GAS CARTS – E736A



FEATURES:

- World beating recovery to less than 0.5 mbar whilst compressing up to 50 bar
- Purifies, dries, and filters SF6 to 0.5 microns
- Can be supplied with or without onboard storage
- Automatic shut off when maximum allowable pressure is reached
- Manual or PLC control
- Choice of oil-less, oil-free or oillubricated SF6 compressors
- Instrumentation grade valves and fittings
- Inlet pressure regulator
- Internal equalization restarting circuit
- Automatic high-pressure shutdown
- High-pressure warning light
- Heavy-duty suction pressure gauge
- Heavy-duty discharge pressure gauge



Enervac servicing carts are designed to meet today's many and varied requirements for efficient SF6 Gas Reclaiming and Handling. Our carts are custom designed using the latest technology to meet the needs of modern gas handling. Simple in operation, limited maintenance, safe, efficient, and economical to operate. Enervac carts are built to the highest quality standards and assure many years of trouble free operation.

APPLICATIONS:

The Enervac SF6 Gas Servicing Cart is designed for the processing of Sulfur Hexafluoride used in high voltage metal clad switch gear, bus ducts, accelerators, circuit breakers and transformers that are charged during normal operation with SF6 Gas as a dielectric. The Cart will perform the following functions;

- Removal of SF6 gas from equipment, liquefaction, and storing of gas in system storage tank
- The system evacuates the serviced equipment for dry out prior to re-charging
- Re-evaporating SF6 gas and refilling evacuated equipment
- Purification of SF6 gas by absorption and removal of decomposition products and moisture

OPTIONAL FEATURES:

- Trailer, caster or skid-mounted
- Aluminum enclosure or roll-up tarpaulin sides
- Optional HMI touch screen with easy 1 touch start/stop function

