



PART NUMBER EXAMPLE:
A26044 # # #

NULL = ALUMINUM
T = 316SS

NULL = STANDARD CONTACTS
GC = GOLD CONTACTS

NULL = CLASS I, DIV 1, APPROVED (US/CAN)
ERNST = CLASS I, DIV 1, APPROVED (US/CAN)

BILL OF MATERIAL

NO.	PART NO.	QTY.	NAME OF PART	MATERIAL	REMARKS
1	CI SAS-16	1	CONTROL AND INSTALLATION DRAWING	N/A	NOT SHOWN
2	IOM-M500.28	1	IOM	N/A	NOT SHOWN
3	E TB 2PCSPLICE	4	SPLICE: CONNECTOR: 2-CONDUCTOR	N/A	
4	G281	1	O RING	BUNA	
5	P1654 P	4	SCREW, DRIVE	STAINLESS STEEL	
6	PER ORDER	2	CLAMP: HOSE	STAINLESS STEEL	
7	V19799 E6 ANN	1	HOUSING: BASE	ALUMINUM	
	V19799 T	1	HOUSING: BASE	316SS	
8	V19860	1	SWITCH: STANDARD	CERAMIC	
	V20435	1	SWITCH: GOLD PLATED CONTACTS	CERAMIC	
9	V20101 E6 ANN	1	HOUSING: CAP	ALUMINUM	
	V20101 T	1	HOUSING: CAP	316SS	
10	V22878 F	1	FITTING: SEAL	BRASS OR NICKEL PLATED BRASS	
	V22878 T	1	FITTING: SEAL	316SS	
11	V22879 E6	1	ENCLOSURE	ALUMINUM	
	V22879 T	1	ENCLOSURE	316SS	
12	V22882	1	LABEL: SAS-16: US/CAN	ALUMINUM	
	V22882 T	1	LABEL: SAS-16: US/CAN	316SS	
	V22883	1	LABEL: SAS-16: US/CAN: EFI	ALUMINUM	
	V22884	1	LABEL: SAS-16: GOLD CONTACT: US/CAN	ALUMINUM	
	V22884 T	1	LABEL: SAS-16: GOLD CONTACT: US/CAN	316SS	
13	V22888 E6	1	NIPPLE: 1/2 NPT	ALUMINUM	
	V22888 T	1	NIPPLE: 1/2 NPT	316SS	
14	X172634	1	SCREW: SET: 6-32 X 1/4	316SS	
15	X172998	1	SCREW: GROUNDING 10-32 X 1/4	STAINLESS STEEL	

REV	DATE	REVISION	BY
4	03/15/2022	UPDATED ASSEMBLY BUILD, REMOVED SHEET 2	SH
3	09/29/2020	UPDATED BOM'S, UPDATE NOTES, ADDED SHEET 2, UPDATED DRAWING FORMAT	SH
2	05/13/2008	NO REVISION HISTORY	SRM

NOTES:
1) AGENCY CONTROLLED DOCUMENT.

MANUFACTURED BY

 16633 FOLTZ PARKWAY
 STRONGSVILLE, OH 44149 USA
 (440) 572-1500 | www.clarkreliance.com
 © Clark-Reliance® LLC. All Rights Reserved.

ASSEMBLY: W/JUNCTION BOX: SAS-16
 US/CAN APPROVAL

JERGUSON®

DRAWN: SH	DRAWING NO.:	REV.:
CHECKED: SRM	A-26044	4
DATE: 03/15/2022		
CDC: 4 : 22-094: SH: 03/15/2022		
MATERIAL: PER ORDER		
PART NUMBER: SEE PART NUMBER EXAMPLE		

TOLERANCES (U.O.N.):
 3 Decimal Places: ± .060"
 2 Decimal Places: ± .090"
 Fractions: ± .045"
 Machined Holes: ± .005"
 Angles: ± 1°
 Finish Marks: ≤ .125 RMS
 (See PES-004 for details.)