

SPECIFICATIONS

DIMENSIONS:

Height: 60" (1500mm)
Width: 24" (600mm)
Depth: 16" (400mm)
Weight: 69lbs (31kg)

STANDARD VOLTAGE:

120V-1PH- 60
220V-1PH -50/60Hz
(other voltages available on request)

SYSTEM PERFORMANCE:

Vacuum pump for evacuation of air
10CFM (17 m³/hr) <0.03
mbar

Enervac International ULC
280 Holiday Inn Drive
Cambridge, Ontario
Canada
N3C 1Z4
(P)1-519-651-1034
(F)1-519-651-1038

www.enervac.com
sales@enervac.com



For more information scan the code!

SF₆ GAS CARTS – ERFU-2



A lightweight, yet rugged, portable unit for the evacuation of gas switchgear, or breaker compartments; and regulated filling using standard SF₆ gas cylinders.

FEATURES:

- Single valve operation
- Large tires for easy movement over gravel yards
- Permanently mounted high capacity, high vacuum pump
- User adjustable regulated gas refilling
- Integral vacuum gauge
- 3 way ball valve for simple switching between evacuation and refilling
- Comes complete with 9.8ft/3m hoses and power cable

APPLICATIONS:

- Evacuate air and moisture prior to filling
- Regulated filling of SF₆ equipment

