

2700G Series

Fuel Gas Coalescer Filter Element

Element Information

2700G

A

Media

Multiple layers of synthetic materials and microglass

Support Layer

Stainless steel wire mesh for mechanical integrity

End Cap Configuration

Double Open Ended

Gasket Material

Viton (Flat)

Efficiency

| | |
|-----|------|
| A = | 0.5μ |
| B = | 0.3μ |
| 1 = | 2μ |
| 6 = | 0.3μ |
| 7 = | 0.5μ |
| 9 = | 5μ |

Dimensions & Weight

| | ID | OD | Length | Weight |
|-----|---------|---------|---------|----------|
| A = | 6-3/4" | 10-1/4" | 24-1/4" | 24 lbs. |
| B = | 11" | 15-3/4" | 24-5/8" | 37 lbs. |
| 1 = | 6-7/8" | 11-1/2" | 28-1/2" | 30 lbs. |
| 6 = | 16-3/4" | 24-1/2" | 36-1/4" | 100 lbs. |
| 7 = | 4-1/4" | 8-3/4" | 20" | 22 lbs. |
| 9 = | 6-3/4" | 10-1/4" | 24-1/4" | 27 lbs. |

Consult Factory



Construction

End Caps: Stainless Steel

Cores: Heavy gage stainless steel perforated sheet

Recommended Operating Conditions

Change out Differential Pressure: 15 PSID

Continuous Maximum Temp.: 400° F

Intermittent Maximum Temp.: 450° F